

# **CYCLO<sup>®</sup> INDUSTRIES, LLC**

## **MATERIAL SAFETY DATA SHEET**

10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881  
Phone: (561) 775-9600

First Aid Emergency: (800) 752-7869 Ext. 10 (USA only)  
Outside USA call collect 1 (312) 942-5969 Ext. 10  
Shipping Emergency: (800)424-9300

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

### **SECTION 1 — PRODUCT IDENTIFICATION**

Product Name: C-13, Cyclo<sup>®</sup> Break•Away<sup>®</sup> Fast Penetrating Oil, 1 gallon  
C-15, Cyclo<sup>®</sup> Break•Away<sup>®</sup> Fast Penetrating Oil, 55 gallon

Hazardous Material Description: DOT - Lubricating Oil, NOI, Class 65  
IMDG - Paraffin Oil, Non Hazardous

HMIS Code: HEALTH=2 REACTIVITY=0 FLAMMABILITY=2

### **SECTION 2 — PHYSICAL DATA**

Boiling Point: >500°F	Specific Gravity: Not available
Vapor Pressure: Not available	Vapor Density (AIR=1): >1
Percent Volatile By Volume (%): 91.62	Percent Solids By Weight: Not applicable
Solubility in Water: Insoluble	pH: Not available
Evaporation Rate (Ether = 1): <1	

## SECTION 8 — SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled:

**LARGE SPILLS:** Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off sources of leak only if it is safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress and contain run-off. Remove with vacuum trucks or pump to storage or salvage vessels. Soak up with absorbent material and place in non-leaking containers.

**SMALL SPILLS:** Take up with absorbent material and place in non-leaking containers. Seal tightly for proper disposal.

Waste Disposal Method: In accordance with local, state and federal regulations.

## SECTION 9 — SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storage:

Store in a well ventilated area away from possible ignition sources.

Other precautions:

Store in a cool, dry, ventilated area away from ignition sources.

Date entered: 5/20/93

Date revised: 6/24/97

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.