



**SECTION 3 — HAZARDOUS INGREDIENTS**

CAS Reg No.	Material	Percentage	TLV (Units)
1330-20-7	Mixed Xylenes (Limited paraxylene content)	40 - 50	100 ppm TWA (435 mg/m <sup>3</sup> ) 150 ppm STEL (655 mg/m <sup>3</sup> )
67-64-1	2-Propanone	25 - 35	750 ppm TLV (1780 mg/m <sup>3</sup> ) 1000 ppm STEL (2380 mg/m <sup>3</sup> ) (ACGIH) 750 ppm PEL (1800 mg/m <sup>3</sup> ) 1000 ppm STEL (2400 mg/m <sup>3</sup> ) (OSHA) 250 ppm TWA (590 mg/m <sup>3</sup> ) (NIOSH)
74-98-6	Propane	8	1000 ppm
100-41-4	Ethylbenzene	1 - 10	100 ppm TWA (435 mg/m <sup>3</sup> ) 125 ppm STEL (545 mg/m <sup>3</sup> )
67-63-0	Isopropanol	5 - 15	400 ppm TWA (980 mg/m <sup>3</sup> ) 500 ppm STEL (1225 mg/m <sup>3</sup> )
78-93-3	Methyl Ethyl Ketone	1 - 10	200 ppm TWA OSHA PEL 300 ppm STEL ACGIH TLV
111-76-2	Butoxyethanol	0 - 5	25 ppm (skin)

**SECTION 4 — FIRE AND EXPLOSION HAZARD DATA**

Flash Point: &lt;-20°F

Method Used: T.C.C.

Extinguishing Media: Chemical, foam, carbon dioxide.

**Special Fire Fighting Procedures:**

The use of self-contained breathing apparatus is recommended for firefighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes.

**Unusual Fire and Explosion Hazards:**

Prolonged exposure to temperatures above 130°F may cause cans to burst.

**SECTION 5 — HEALTH HAZARD DATA****Effects of Overexposure:**

Ingestion: Harmful or fatal.  
Inhalation: May cause breathing difficulties.  
Skin Contact: May cause irritation.  
Eye Contact: May cause irritation.

**First Aid Procedures:**

Ingestion: DO NOT induce vomiting. Contact a physician immediately  
Skin Contact: Wash with soap and water.  
Inhalation: Remove to fresh air. Administer oxygen if needed.  
Eye Contact: Flush with plenty of water for at least 15 minutes. Contact a physician if irritation persists.

**SECTION 6 — REACTIVITY DATA**

Stability: Stable

Conditions to Avoid: Temperatures above 130°F.

Incompatibility (materials to avoid): None known

Hazardous Decomposition Products: None known

Hazardous Polymerization: Will not occur.

**SECTION 7 — SPECIAL PROTECTION INFORMATION**

Respiratory Protection: Not normally required.

**Ventilation:**

Local Exhaust Rate: Recommended

Special: None

Mechanical (General): Acceptable

Protective Gloves: Rubber gloves.

Eye Protection: Safety glasses

Other Protective Equipment: None

**SECTION 8 — SPILL OR LEAK PROCEDURES****Steps To Be Taken In Case Material Is Released or Spilled:**

Pick up excess with absorbent material and discard in accordance with regulations. Flush surfaces with IPA and then rinse with soap and water.