

authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Waste Disposal Method: Waste must be disposed of according to local, State, and Federal regulations. Do not pump in any sewers. Contains petroleum distillates, ( petroleum solvents) classified as hazardous was under EPA 40 CFR based on the characteristics of ignitability, Code D001.

CYCLO INDUSTRIES, INC.  
(subsidiary of Accra Pac Group, Inc.)  
MATERIAL SAFETY DATA SHEET

10190 Riverside Dr., Palm Beach Gardens, Fl. 33410-4881

CERCLA (Superfund)Reportable Quantity: NA

Shipping Emergency: (800) 424-9300

RCRA Hazardous Waste Number : (40 CFR 261.33) NA

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL , STATE, and COMMUNITY RIGHT TO KNOW regulations. Also make this information available to any employees who requests it.

Volatile Organic Compound (VOC) ( as packaged minus water):

\*\*\*\*\*  
SECTION 9 - SPECIAL PRECAUTIONS  
\*\*\*\*\*

Precautions to be taken in handling and storage:  
Store containers in a cool dry well ventilated area away from all ignition sources and strong oxidizers.

Other precautions: Keep this and all chemicals out of the reach of children. Avoid breathing oil mist, and prolonged or repeated contact with skin.

\*\*\*\*\*

Date entered: 10-6-92

Date revised: 10-6-92

Cyclo Industries, inc., provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, Inc., makes no representations, or warranties, either express or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, CYCLO Industries, inc., will not be responsible for damages resulting from use of or reliance upon this information.

If CYCLO Industries, Inc. considers the formula of this product to be a trade secret, the exact chemical names of the ingredients(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists, and other health professionals.

\*\*\*\*\*  
SECTION 1 - PRODUCT IDENTIFICATION  
\*\*\*\*\*

Product name: POWER STEERING FLUID (c 27, 28, 29)

Chemical Name: NA

Hazardous Material Description: Petroleum distillate (Petroleum solvent)

Chemical Family: Solvent Formula:NA

\*\*\*\*\*  
SECTION 2 - PHYSICAL DATA  
\*\*\*\*\*

Boiling Point: >425°F Specific Gravity:0.876

Vapor Pressure:70° F < 0.1 Vapor Density: >8 (air =1)

Percent Volatile by volume: (%) NA

Percent Solids by weight: (%)NA

Solubility in water:Negligible pH: NA

Evaporation rate:(<0.01 ) :

Appearance and Odor: Amber colored liquid, lube oil odor.

\*\*\*\*\*  
SECTION 3 - HAZARDOUS INGREDIENTS  
\*\*\*\*\*

Components CAS Number Percent PEL/TVA

This material is not known to contain greater than 0.1% of any carcinogen required to be listed under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

HMIS and NFPA Codes: Health: 1 Flammability: 1 Reactivity: 0

\*\*\*\*\*  
SECTION 4- FIRE AND EXPLOSION HAZARD DATA  
\*\*\*\*\*

Flash point: >365° F Method used:Cleveland Open Cup

Extinguishing Media: Water, fog, or spray, dry chemical, alcohol foam, or carbon dioxide.

Special Fire Fighting Equipment: Use air-supplied breathing equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapors or fumes.

Unusual Fire and Explosion Hazards:

Do not mix or store with strong oxidants like chlorine, or concentrated oxygen. Empty product containers contain residue, do not pressurize, heat, weld, or expose such containers to flames. They may explode and cause injury or death.

\*\*\*\*\*  
SECTION 5 - HEALTH HAZARD DATA  
\*\*\*\*\*

EFFECTS OF OVEREXPOSURE

Ingestion:If ingested, call a physician.

Inhalation: Vapors are minimal due to physical properties; a single exposure is not likely to be hazardous.

Skin Contact: Prolonged or repeated exposure may cause skin irritation. May cause severe response if skin is abraded ( cut or scratched.)

Eye Contact: May cause irritation.

Threshold Limit Value:NA

FIRST AID PROCEDURES:

Ingestion:In ingested, call a physician.

Skin Contact: Remove contaminated clothing, and wash skin with soap and water

Inhalation: Remove to fresh air if effects occur. Consult a physician if necessary.

Eye Contact:Flush eyes with plenty of water for at least fifteen minutes.

\*\*\*\*\*  
SECTION 6 - REACTIVITY DATA  
\*\*\*\*\*

Stability:Stable

Conditions to Avoid: Accumulation of vapors.

Incompatibility: (Materials to avoid) Strong oxidizers

Hazard Decomposition Products: Fumes, smoke, and carbon monoxide and sulfur oxides in case of incomplete combustion.

Hazardous Polymerization: Will not occur.

\*\*\*\*\*  
SECTION 7 - SPECIAL PROTECTION INFORMATION  
\*\*\*\*\*

Respiratory Protection: A NIOSH approved respirator for organic vapors should be worn if needed.

Ventilation: Use local exhaust if needed to control vapor at elevated temperatures.

Local Exhaust rate: Recommended Special:NA

Mechanical ( General): Recommended

Protective Gloves: Resistant plastic or rubber

Eye Protection: Chemical splash goggles

Other protective equipment: Provide suitable training for those working with Power Steering Fluid.

\*\*\*\*\*  
SECTION 8 - SPILL OR LEAK PROCEDURES  
\*\*\*\*\*

Steps to be taken in case material is released or spilled:  
Recover free liquid. Add absorbent (sand, earth, sawdust, etc) to spill area. Remove all sources of ignition. Minimize breathing vapors. Open all windows and doors. Keep petroleum products out of sewers and watercourses by diking or impounding. Advise