

CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881

Phone: (561)775-9600 Shipping Emergency: (800)424-9300
In Emergency: (800)752-7869 Ext.10 (USA Only)
Outside USA call collect (312)942-5969 Ext.10

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 — PRODUCT IDENTIFICATION

Product Name: C-35 RUBBERIZED UNDERCOATING

Chemical Family: Mixture

Hazardous Material Description: Consumer Commodity ORM-D

HMIS Code: HEALTH=2 FLAMMABILITY=4 REACTIVITY=0

Percent V.O.C. By Weight: 57.25%

SECTION 2 — PHYSICAL DATA

Boiling Range: 313 - 386°F Specific Gravity (H₂O=1): 1.12

Vapor Pressure: 2 mmHg Vapor Density (AIR=1): 4.9

Percent Volatile By Volume (%): 100.0% pH: Not determined

Solubility in Water: Not soluble in water. Evaporation Rate (n-butyl acetate=1): 0.21

Appearance and Odor: Black, viscous liquid - strong solvent odor in a hydrocarbon propellant.

SECTION 5 — HEALTH HAZARD DATA continued

Threshold Limit Value: Not determined.

First Aid Procedures:

- Ingestion: Do not induce vomiting. Give CONSCIOUS victim large quantities of water. Call a physician immediately. NEVER give water to unconscious victim.
- Skin Contact: Wash with soap and water. If irritation persists, contact a physician.
- Inhalation: Remove to fresh air. Get immediate medical attention. If breathing has stopped, begin artificial respiration.
- Eye Contact: Flush with water for 15 minutes. Obtain medical attention if necessary.

SECTION 6 — REACTIVITY DATA

Stability: Stable.

Conditions to Avoid: Excessive heat, open flame.

Incompatibility (materials to avoid): Strong Oxidizing agents.

Hazardous Decomposition Products: Carbon dioxide or carbon monoxide.

Hazardous Polymerization: Cannot occur.

SECTION 7 — SPECIAL PROTECTION INFORMATION

Respiratory Protection: Wear organic vapor air purifying respirator.

Ventilation: Strong general or local exhaust ventilation.

Local Exhaust Rate: Not determined. Mechanical (General): Recommended.

C-35 Rubberized Undercoating MSDS – Page Five

Date entered: 5/28/92

Date revised: 5/5/95

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.