

L6950

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 127730
IDENTITY: MULTI-PURPOSE LUBE II 20A Revision Date: 06/01/2007

Section I

Manufacturer's Name: FEHR BROTHERS *** Telephone Numbers:
Address: 895 KINGS HIGHWAY Emergency:
SAUGERTIES 800/255-3924
State: NY Zip Code: 12477 Information:
845/246-9525

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	___
LOW ODOR BASE SOLVENT	64741-85-1	100 PPM	100 PPM	100 PPM	___
NAPHTHENIC PETROLEUM DIST	64742-53-6	5 MG/M3	5 MG/M3		___
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	___

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Specific Gravity (water=1) 0.82
Vapor Pressure(mm Hg) N/A Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 0 % (Butyl Acetate=1)
Appearance and Odor: LIGHT BROWN VISCOUS LIQUID, ETHEREAL ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):>100 TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A
FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 127730

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F
 Stable: X
 Incompatibility (Materials to Avoid): NONE KNOWN

Hazardous Decomposition or Byproducts: MAY FORM CO₂, CO, CHLORINE, HCL AND PHOSGENE.

Hazardous Polymerization: May Occur: Will Not Occur: X
 Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
 Health Hazards (Acute and Chronic):
 INHALATION: DIZZINESS-PROLONGED MAY LEAD TO UNCONSCIOUSNESS. EYES: STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED DEFATTING.
 INGESTION: VOMITING, DIZZINESS, NAUSEA, INTESTINAL CRAMPING.
 Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
 Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: CONSULT PHYSICIAN

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.
 Ventilation: Local Exhaust:ADEQUATE
 Mechanical: N/A Special: N/A
 Other: N/A
 Protective Gloves:CHEMICAL RESISTANT GLOVES SUCH AS VITON OR PVA.
 Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
 Other Protective Clothing or Equipment:
 NONE.
 Work/Hygienic Practices:
 WASH HANDS AFTER USE.