



MATERIAL SAFETY DATA SHEET

SECTION I - SUPPLIER INFORMATION

Product Name: Pitt Penn Premium Windshield Washer Solvent -20°F
Product Number: 803660, 803660N, 803675 & 866060
Bulk Stock Number: 027875

Synonyms: Methanol, Methyl Alcohol, Wood Alcohol, Columbian Spirits, Carbinol
Chemical Formula: CH₃OH - Mixture of water, Methanol, and dye (The Solution)
CAS Name & Number: Methanol (67-56-1)
Chemical Family: Aliphatic Alcohol

Supplier's Name & Address: Pitt Penn Oil Co.
426 Freeport Road
P.O. Box 296
Creighton, PA 15030
(724) 226-2712

Emergency Phone Number: Chem Tel, Inc. 1-800-255-3924 (24 hours)

Current Issue Date: September 15, 2003
Date of Origination: October 3, 2000

SECTION II - HAZARDOUS INGREDIENT INFORMATION

<u>Ingredient</u>	<u>CAS #</u>	<u>% vol</u>	ACGIH TWA (Units)	ACGIH STEL (Units)	OSHA TWA (Units)
Methyl Alcohol	67-56-1	33 - 35%	200 ppm	200 ppm	200 ppm
Water	7732-18-5	65 - 70%	NA	NA	NA

There is a notation that indicates that absorption through the skin can contribute significantly to overall exposure.

Incompatibility: formaldehyde) may be released in a Methanol fire.
Strong oxidizing agents such as nitrates,
perchlorates or sulfuric acid.

SECTION VI - HEALTH HAZARD DATA/FIRST AID

Effects of Overexposure: Methanol is a poisonous, narcotic chemical that can affect the body through inhalation, ingestion, and perhaps prolonged or repeated skin contact. Absorption by inhalation or ingestion is rapid and excretion is much slower than for ethyl alcohol, resulting in delayed effects or compounding of effects by repeated exposure. It is important to be aware that after ingestion or inhalation, initial symptoms may be only that of mild intoxication, but may become severe after 12 to 18 hours. Toxic effects are exerted upon the central nervous system, especially the optic nerve. Ingestion can produce blindness; 100-250 ml can be fatal. Symptoms of overexposure include dizziness, visual impairment, nausea, respiratory failure, muscular in coordination and narcosis. Prolonged or repeated skin contact may cause dermatitis, erythema, scaling, and possibly systemic effects. See also Section VII.

ROUTES OF ENTRY/EMERGENCY AND FIRST AID PROCEDURES

Eyes: Wash eyes immediately with running water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible.

Skin: Remove contaminated clothing and wipe excess off. Wash affected area with soap and water; apply skin lotions. If skin irritation persists, get medical attention.

Inhalation: Remove victim to fresh air at once. Restore and/or support breathing as required. Keep victim warm and at rest. Get medical attention as soon as possible. Prevent exposure to Methanol for seven (7) days.

Ingestion: Get medical attention immediately. Induce vomiting with one (1) tablespoon of Ipecac or by touching the back of the throat (ONLY IF CONSCIOUS). Once vomiting has occurred, have the patient drink milk, water, or a solution of sodium bicarbonate (baking soda) in water - two (2) teaspoons per glass.

Reproductive Effects: Reported to cause birth defects in rats exposed to 20,000 ppm

Tetratogenicity: No

Metagenicity: No

Pitt Penn Oil Co.

Product Name: Pitt Penn Premium Windshield Washer Solvent -20°F

Page 4

Carcinogenicity: Not listed with IARC, NTP, ACGIH or OSHA as a carcinogen.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING

Precautions to be Taken in Handling and Storage:

Ground and electrically interconnect containers for transfer. Use spark proof tools. No smoking in areas of use or storage. Avoid prolonged or repeated breathing of vapor or contact with skin. Avoid contact with eyes. Contact lenses should not be worn while handling Methanol. Eye wash stations and safety showers should be available in area of use. Do not ingest! Store in a well-ventilated, fireproof area, away from sources of heat, open flame, and ignition.

Other Precautions: Provide preplacement medical exams for industrially exposed workers, with emphasis on neurological and visual functions, liver and kidney systems. Provide suitable training to those working with Methanol. Monitor the workplace. Keep records.

Registrations/Certifications: Not applicable

NOTE: Most of these requirements are for Methanol. Since our solution is 33 - 35% by volume Methanol, the requirements listed above are very strict and should be followed closely.

SECTION VIII - SPECIAL PROTECTION AND CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Eye Protection: Safety glasses with side shields or face shield.

Respiratory Protection: Any air supplied respirator or self-contained breathing apparatus.

Only NIOSH or OSHA approved equipment should be used.

Other: Impervious aprons, boots and face shields (8-inch min.) where splashing can occur.

VENTILATION

Local Exhaust: To meet TLV requirements, local exhaust should be used where vapor exposure is likely.

Mechanical (general): Controls must be spark proof and explosion proof.

Special: Not applicable

Other: Not applicable

SECTION IX - HANDLING OF SPILLS AND LEAKS

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

1. Remove all ignition sources.
2. Provide adequate ventilation.
3. Small quantities may be absorbed on paper towels. Evaporate in a safe place (such as fume hood). Burn paper in an approved incinerator or open pit away from buildings and people. Large quantities can be collected and atomized in a suitable combustion chamber. Spills in sensitive areas may be diluted and flushed to ground with a water spray. Do not flush to sewer or other confined space.
4. Spills should be reported according to Federal, State and Local regulations.

Waste Disposal Methods: Absorb in vermiculite, dry sand, earth or a similar material and dispose in a secured sanitary landfill or dispose of via a licensed waste solvent disposal company.

Clean Water Act Requirements: Not applicable

Resource Conservation and Recovery Act (RCRA) Requirements:

Methanol is assigned a hazardous waste number of U154 under 3001.

It is considered a toxic waste.

SECTION X - TOXICOLOGICAL/ECOLOGICAL INFORMATION

Oral: Human LD (Lo) - 240 mg/kg
Dermal: Monkey LD (Lo) - 500 mg/kg
Inhalation: Human TC (Lo) - 86,000 mg/m³ - lacrimation; cough, other changes to lungs, thorax or respiration.
Carcinogenicity: Not listed in Second Annual Report on Carcinogens, 1981, NTP.
Other Pertinent Data: Recommended std-air: TWA 200 ppm; C1 800 ppm/15m

SECTION XI - TRANSPORTATION DATA

D.O.T.: Proper Shipping Name - Methyl Alcohol Solution
Hazard Class - None
Label Required - None
Identification Number - Not Applicable
Other Pertinent Information - See 45 CFR 172.101, page 34625

Pitt Penn Oil Co.

Product Name: Pitt Penn Premium Windshield Washer Solvent -20°F

Page 6

SECTION XII - REGULATORY INFORMATION

FDA: Regulated under 21 CFR 176.200 (d) (3) as a component of defoaming agents which may be safely used as components of articles intended for use in producing, manufacturing, packing, processing, preparing, treating, packaging, transporting or holding food. Also regulated under 176.210 as a component of defoaming agents used in the manufacture of paper and paperboard. Approved as component of paper and paperboard in contact with dry food. [See 176.180 (b) (2)] Listed under 175.105 for use as component of adhesives.

USDA: Information unknown at time of publication.

TSCA: CAS # 67-56-1

WHMIS: Canada B2, D1A

NFPA Rating: Health - 1 Fire - 3 Reactivity - 0

SECTION XIII - USER INFORMATION

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation, and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable Federal, State and Local laws and regulations.

Relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading, this information relates to the material designated and may not be valid for such material used in combination with any other materials or in any process.