

1-11-07
TO NEW LIFE T.P.
ATTN LEAH HERB

06/26/01

SEAL-GAP COMPANY
phone: 352-589-0406
P.O. BOX 696
EUSTIS
FL 32727-0696

Dear Customer:

We are pleased to enclose for your use the following Material Safety Data Sheet(s) which contains health and safety information.

This takes precedence over and supercedes any previous Material Safety Data Sheet(s) you may have for this product.

Effective 1 January 1989, a person who sells or otherwise distributes a mixture or trade name product containing a toxic chemical (i.e., a chemical or member of chemical category in 40 CFR PART 372) must provide written notice to the recipient with the first shipment in each calendar year. This is pursuant to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). The attached MSDS is supplied to you pursuant to these legal requirements. Please note that if you repackage or otherwise redistribute this product a notice including the SARA 313 information should be sent to the recipients.

MSDS are an integral part of the hazard communication and employee information and training programs required of employers under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This MSDS, as all previously furnished MSDS, is the result of the work of a group of specialists including toxicologists, physical chemists and information specialists. It was prepared only after a careful review of the information in our own files and that available in generally accessible public literature. It contains valuable health and safety information which you should use in developing safe handling procedures for your employees. We urge you to send this MSDS to the individuals in your organization responsible for health and safety practices, and to notify your employees, customers, agents, and contractors of the information so that they will be fully informed regarding health, safety, and environmental protection measures.

If you have any questions or require additional information in the storage handling, use or disposal of this product, please contact us.

Attachment

ENCLOSED COVER LETTER AND 6 PAGES M.S.D.S
FOR SEAL-GAP ROOF SEALER A.H.55-A

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
 Version Number
 MSDS Date: JUN-26-2001
 Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: SEAL-GAP ROOF SEALER # AH-55-A
 Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPI: B

Company name: SEAL-GAP COMPANY
 phone: 352-589-0406
 P.O. BOX 696
 EUSTIS
 FL 32727-0696

Contact: Safety Officer
 Emergency Phone (24 hour) CHEMTREC
 (800) 424-9300
 Chemtrec (outside-USA) (703) 527-3887

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
HEPTANE	142-82-5	15 - 25	Y
PETROLEUM NAPHTHA	64742-89-8	15 - 25	Y
XYLENE	1330-20-7	< 5.0	Y

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Medium viscosity sealant
 Appearance/Color: Aluminum
 Solubility (in water): insoluble
 pH Value, +/- .3: Not Applicable
 Boiling Range: 180.°F - 280.°F (82.22°C - 137.78°C)
 Vapor Pressure (mmHg): over 40. @ 68.°F (20.°C)
 Evaporation Rate: 2.5 times Faster than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight: approx. 55.%
 % Volatile, Volume: approx. 65.%
 Specific Gravity: 0.94641

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
 Version Number
 MSDS Date: JUN-26-2001
 Page Number: 2

VOC (less H2O or exempt) 500 gr/L
 Heavy Elements (ppm) 0.

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash, UEL, LEL for solvent only)

Flammability Class I B
 Flash Range: 21.°F (-6.11°C)
 Tag Closed Cup
 Explosive Range (LEL/UEL): 0.9%
 6.7%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
 Use water to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
 operated in pressure demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Water may be unsuitable except as a cooling agent. Use fog nozzle.
 Any closed container may rupture when exposed to extreme heat.
 Solvent vapors are heavier than air and travel along the ground.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH...

Inhalation? Yes | Skin? Yes | Ingestion? Yes

TARGET ORGANS...

Normal Exposure -- Xylene: Eye, Skin
 -- Petroleum Naphtha: Eyes, Skin
 Overexposure -- Xylene: Central Nervous System, Respiratory
 Tract, May aggravate pre-existing heart
 conditions. May cause adverse health
 affect on Kidney and Liver on chronic
 overexposure.
 -Petroleum Naphtha: Central Nervous System, Nose &
 Throat Irritation, Lung, Liver

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
Version Number
MSDS Date: JUN-26-2001
Page Number: 3

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate irritation, defatting, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage and mucous membrane irritation.
INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing.

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
 Version Number
 MSDS Date: JUN-26-2001
 Page Number: 4

 Cover with absorbent. Scoop into sealable safety container.
WASTE DISPOSAL METHOD:
 Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
HEPTANE	400.00 PPM	N/est	N/est	N/est	400.00 PPM
PETROLEUM NAPHTHA	300.00 PPM	N/est	N/est	400.00 PPM	300.00 PPM
XYLENE	100.00 PPM	N/est	150.00 PPM	150.00 PPM	100.00 PPM

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.
 Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely.
 Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.
 Keep out of reach of children.
 Keep container closed while not in use.
 Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.
 Use only in a well ventilated area.

 N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
 Revision Number: 1
 Issue Date: SEP-11-2001
 Page Number: 5

SECTION IX - TRANSPORT INFORMATION:

DOT CLASSIFICATIONS FOR ONE GALLON AND UNDER CONTAINERS

DESCRIPTION: ORM-D, Consumer commodity
 CLASS/ UN NO.: none
 DOT LABEL: ORM-D (Adhesives)
 IMDG class: 3.1
 IMDG BOL: Adhesive, 3, UN1133, PG III, LTD QTY

DOT CLASSIFICATIONS for OVER 1 GALLON size CONTAINERS

DESCRIPTION: Adhesive
 CLASS: Class 3, Packing group III
 DOT LABEL: Flammable Adhesive, UN 1133
 IMDG CLASS: 3.1
 IMDG BOL: Adhesive, 3, UN1133, PG III

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
XYLENE	1330-20-7	< 5.0

This material fits the EPA Hazard Category definition of Immediate (Acute) and Delayed (Chronic) Health Hazards and Fire Hazard under SARA Sections 311, 312.

Chemical ingredients are listed on the TSCA inventory.
 California PROP. 65 Chemicals: none known

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be

MATERIAL SAFETY DATA SHEET

MSDS Name: SEAL-GAP ROOF SEALER # AH-55-A
Version Number
MSDS Date: JUN-26-2001
Page Number: 6

reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and the user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health and safety of the users of this material.