

015-516-011

Spray Products Corporation
P.O. BOX 737
Norristown, PA 19404
Product Information: 610-277-1010

Product Name: Nuts Off 075-516

Revision Date: 2/2/07
Supersedes Date: 1/1/06

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Type: **Lubricant/Penetrant**
Product Name: **Spray Products Nuts Off**
Part Number(s): **SP-075-516**

Emergency Contact: **Chemtrec**
Phone (24 hours): **(800) 424-9300**

Section 1 - Identification of Product

COMMON NAME (used on label)(Trade Name & Synonyms): **Spray Products Nuts Off Penetrating Oil**
CAS. NUMBER: See Section 2
CHEMICAL NAME: N/A
CHEMICAL FAMILY: N/A
FORMULA: N/A

| | | |
|------------------------|------------------------|---|
| HMIS RATINGS | Minimal Hazard | 0 |
| | Slight Hazard | 1 |
| Health: 1 | Moderate Hazard | 2 |
| Irritability: 3 | Serious Hazard | 3 |
| Reactivity: 0 | Severe Hazard | 4 |
| Personal Protection: B | Gloves, Safety Glasses | B |

Section 2 - Hazardous Ingredients

Principal Hazardous Component(s)

| CHEMICAL AND COMMON NAME(S) | CAS. # | OSHA PEL | ACGIH TLV | VAPOR | LEL | UEL | FLASH POINT DEG. F | APPROX WT % |
|-----------------------------------|------------|-------------|--------------|--------------------------|------|-----|-----------------------|----------------|
| | | | | PRESSURE @ 25 DEG. C. | | | | |
| Mineral Spirits | 8052-41-3 | 100ppm | 100ppm | 2.0mmHg | 0.7 | 6.0 | 105(TCC) | 47 |
| Heavy Naphthenic Oil | 64742-52-5 | 5 mg/m3 | 5 mg/m3 | <1mmHg | n/a | n/a | >300 (COC) | 30 - 35 |
| Hydrotreated Light Distillate* | 64742-47-8 | n/a | n/a | 0.07mmHg | 0.5 | 4.9 | 177 (PMCC) | 15 - 20 |
| Carbon Dioxide | 124-38-9 | 5000ppm | | 1 atm. | None | | None | <10 |

*ExxonMobil recommends a TWA of 1200 mg/m3

Section 3 - Physical Data

BOILING POINT (Deg. F): Concentrate Range: 315 - 550

SPECIFIC GRAVITY (Water = 1): Concentrate: 0.83

VAPOR PRESSURE (mmHg): See Section 2

Spray Products Corporation

P.O. BOX 737

Norristown, PA 19404

Product Information: 610-277-1010

Product Name: Nuts Off 075-516

Revision Date: 2/2/07

Supersedes Date: 1/1/06

PERCENT VOLATILE ORGANIC COMPOUNDS: <50%

VAPOR DENSITY (Air = 1): >1

EVAPORATION RATE (BA = 1): >1

SOLUBILITY IN WATER: Negligible

REACTIVITY IN WATER: None

APPEARANCE AND ODOR: CONCENTRATE: Amber liquid, petroleum odor at high concentrations;

PROPELLANT: Colorless, odorless gas; **FINISHED PACKAGE:** Pressurized containers.

Section 4 - Fire & Explosion Hazard Data

FLASH POINT: See Section 2

FLAMMABLE LIMITS IN AIR - % BY VOLUME: See Section 2

EXTINGUISHER MEDIA: Water fog, dry chemical, carbon dioxide

AUTO-IGNITION TEMPERATURE: Unknown

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure build-up and possible bursting when exposed to high temperatures. Firemen should wear self-contained, positive pressure, respiratory equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Do not use or store near heat or ignition sources. Containers may burst at temperatures above 130 deg. F.

Section 5 - Health Hazard Data

THRESHOLD LIMIT VALUE: See Section 2

SIGNS AND SYMPTOMS OF EXPOSURE:

EYE CONTACT:

Contact with liquid or mist may cause irritation. Vapors may irritate eyes;

SKIN CONTACT:

Prolonged contact may cause irritation, defatting of skin;

INHALATION:

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: Headache, dizziness, nausea, staggering gait, confusion, and unconsciousness.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. **INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS OF THE CAN MAY BE HARMFUL OR FATAL;**

INGESTION:

Aspiration may cause rapid absorption through the lungs, which may result in systemic effects.

IMPORTANT NOTE: REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS MAY LEAD TO PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. EYE WATERING, HEADACHES, NAUSEA, DIZZINESS AND LOSS OF COORDINATION ARE SIGNS THAT SOLVENT LEVELS ARE TOO HIGH. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

EMERGENCY AND FIRST AID PROCEDURES:

- INHALATION:** Remove to fresh air. If not breathing, give mouth-to-mouth. If breathing is difficult, give oxygen. Do not give epinephrine or similar drugs. Call a physician.
- EYES:** Flush with water for at least 15 minutes. Get medical assistance if irritation persists.
- SKIN:** Wash off in flowing water or shower. Remove contaminated clothing and wash before reuse.
- INGESTION:** Do not induce vomiting. Call a physician immediately.

Section 6 - Reactivity Data

- STABILITY:** Stable
- CONDITIONS TO AVOID:** Avoid any excessive heat, ignition sources, open flames, or other high temperatures which induce thermal decomposition.
- INCOMPATIBILITY (Materials to Avoid):** Strong oxidizing agents
- HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide.
- HAZARDOUS POLYMERIZATION:** Will not occur.
- CONDITIONS TO AVOID:** Not Applicable

Section 7 - Spill or Leak Procedures

- STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**
- SMALL SPILLS:** Remove ignition sources. Mop up, wipe up, or soak up immediately. Use proper protective equipment.
- LARGE SPILLS:** Evacuate area. Remove ignition sources. Contain liquid; transfer to closed containers; keep out of water supplies.
- WASTE DISPOSAL METHODS:** Dispose in accordance with Federal, State, and Local regulations. Do not incinerate closed or empty containers.

Section 8 - Special Protection Information

- RESPIRATORY PROTECTION:** NIOSH or Bureau of Mines approved organic vapor-type respirator is required in absence of proper environmental control.
- VENTILATION:**
- LOCAL EXHAUST: To keep below TLV
 - MECHANICAL (General): To keep below TLV
 - SPECIAL: None
 - OTHER: None
- PROTECTIVE GLOVES:** Solvent resistant gloves - impervious gloves
- EYE PROTECTION:** Safety glasses or goggles
- OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None reasonably foreseeable.

Spray Products Corporation

P.O. BOX 737

Norristown, PA 19404

Product Information: 610-277-1010

Product Name: Nuts Off 075-516

Revision Date: 2/2/07

Supersedes Date: 1/1/06

Section 9 – Special Precautions

PRECAUTIONS TO BE TAKEN

IN HANDLING AND STORAGE:

Do not store above 120 Deg. F. Do not use or store near any open flames or ignition sources.

OTHER PRECAUTIONS:

FLAMMABLE. Do not use or store near open flames, heat, or any sources of ignition. Contents under pressure. Do not puncture or incinerate. Vapors are heavier than air and will collect in low areas.

Section 10 - Regulatory Information

SUBJECT TO SECTION 313 OF SARA TITLE III: No.

ALL CHEMICAL COMPONENTS ARE LISTED IN THE TSCA INVENTORY.

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: NATIONAL TOXICOLOGY PROGRAM: No

I.A.R.C. MONOGRAPHS: No

OSHA: No

TLV PERMISSIBLE EXPOSURE LIMIT: See Section 2

TLV THRESHOLD LIMIT VALUE: See Section 2

OTHER EXPOSURE LIMITED USED: None

Section 11 - Other Information

TRANSPORTATION INFORMATION – DOMESTIC GROUND

| | |
|-----------------|---------------------------|
| Shipping Name: | Consumer Commodity |
| Hazard Class: | ORM-D |
| UN Number: | N/A |
| Packing Group: | N/A |
| Hazard Label: | None |
| Carton Marking: | Consumer Commodity, ORM-D |

Disclaimer

SPRAY PRODUCTS CORPORATION believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Persons receiving this information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY SPRAY PRODUCTS CORPORATION.